



ECO

Rubber flooring



Topflor

The ultimate flooring
The ultimate performance



2101



2102



2103



2104



2105



2106



2107



2108



2109



2110



2111



2112



2113



2114



2115



2116



2117



2118



2119



2120



2121



2122



2123



2124



2125



2126



2127



2128



2129



2130



2131



2132

ECO



Rubber flooring with smooth tone-in-tone granular design

PRODUCT FEATURES

resistant to chemicals | no damages from short-time exposures to solvents, acids and alkaline agents
skin disinfectants such as iodine | containing products can be removed easily
bacteriostatic and fungistatic property
dimensionally stable when installed, thus can be installed without joint | sealing even in large areas

APPLICATION

airport, hospital, school, library, office building etc | corridor, escape route, patient room, ward station intensive care unit, visitor room, administration office

TECHNICAL DATA

	Overall thickness	EN 428	2 mm
	Roll size	EN 426	1.22m X 15m
	Total weight	EN 430	3600 g/m ²
	Reaction to fire	EN 13501-1	Class Bfl-s1
	Electrical resistance	EN 1815	≤ 2kV
	Slip resistance	DIN 51130	R 9
	Abrasion resistance	ISO 4649	130mm ³
	Residual indentation	EN 433	0.05mm
	Dimensional stability	EN 434	± 0.3%
	Colour fastness	EN 20 105-B02	≥ 6
	Resistance to chemicals	EN 423	Good
	Castor chair test	EN 425	Suitable
	Impact sound insulation	EN ISO 717-2	8 dB

CE MARKING



EN 14041

